

TSE DP-20-4H 4 DRUM PULLER

WITH 2,000 lb. FULL DRUM CONTINUOUS LINE-PULL



SPECS

DESCRIPTION A VERSATILE, HYDRAULICALLY POWERED FOUR DRUM PULLER DESIGNED FOR MEDIUM DISTRIBUTION STRINGING. IT CAN ALSO BE USED AS A PILOT LINE WINDER FOR HEAVIER DISTRIBUTION. DIESEL ENGINE POWER THROUGH A HYDRAULIC DRIVE TRAIN. A DIAMOND-CUT LEAD-SCREW LEVELWIND, ACCOMMODATING ONE REEL AT A TIME. EACH REEL IS EQUIPPED WITH A MECHANICAL CLUTCH TO ALLOW SELECTIVE REEL ROTATION AND A BRAKE TO CONTROL OVERSPIN. THE MAXIMUM LINEPULL CAN BE PRESET PRIOR TO PULLING SO THAT THE REEL DRIVE WILL STALL IF A RESTRICTION OCCURS WHILE PULLING. CENTRAL OPERATORS CONSOLE ALLOWS THE OPERATOR COMPLETE CONTROL OF THE PULLING OPERATION WITH OPTIMUM VISIBILITY. STANDARD FEATURES 2,000 LBS. LINE PULL CAPACITY ON A SINGLE FULL DRUM, HYDROSTATIC PULLING SYSTEM WITH OIL COOLER, FOUR PULLING REELS, EACH WITH A CAPACITY FOR 6,000' OF 1/2" OR 10,000' OF 3/8" ROPE, INFINITELY VARIABLE LINESPEED AND LINEPULL CONTROL, MECHANICAL CLUTCH AND BRONZE BRAKE FOR EACH REEL, SPRING APPLIED HYDRAULIC PRESSURE RELEASED HOLDING BRAKE, OPERATORS SEAT AND PROTECTIVE SCREEN. SWING OUT. AUTOMATIC LEAD-SCREW LEVELWIND.

ENGINE:

KUBOTA 3 CYLINDER DIESEL ENGINE, 27 HP., MODEL-V1505-ET04 30 GALLON FUEL TANK

TRAILER:

SINGLE 8,000 LB. AXLE, SINGLE WHEEL, 215/75R17.5 TIRES, 8 HOLE 17.5 X 6.75 RIMS, ELECTRIC BRAKES MANUAL TONGUE JACK, (2) REAR DROP DOWN LEG STABILIZERS, ADJUSTABLE PINTLE HITCH, FULL COVER FENDERS, DOT LIGHTING, 7 PRONG ROUND TRAILER PLUG.

DIMENSIONS:

15' LONG 8' WIDE 6' 4" TALL 5,800 LBS. WITH ROPE

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL







888-925-0858 www.customtruck.com

