



TEREX HI-RANGER TM125 BUCKET TRUCK

125' NON-OVERCENTER MATERIAL HANDLING AERIAL DEVICE



SPECS

125' WORKING HEIGHT

52' SIDE REACH

CONTINUOUS UNRESTRICTED ROTATION

AVAILABLE ON MANY DIFFERENT CHASSIS MAKES, MODELS

BOTH ARTICULATING BOOM & HYDRAULIC EXTENSIONS OF UPPER & LOWER BOOM

90 DEGREES OF LOWER BOOM ARTICULATION

168 DEGREES OF UPPER BOOM ARTICULATION

HI-STRENGTH STEEL BOOM CONSTRUCTION

LOWER BOOM INSULATION GAP: 20"

UPPER BOOM: 14' CLEAR INSULATION

CONTROL-PLUS 4-FUNCTION SINGLE STICK CONTROL

HYDRAULIC/ELECTRIC PLATFORM LEVELING SYSTEM

35" X 57" X 42" FIBERGLASS PLATFORM ROTATING D-SHAPED-STYLE W/

GROUND ACCESS, 180 DEGREE HYDRAULIC ROTATOR, 800 LBS. PLATFORM CAPACITY

UPPER/LOWER CONTROL SELECTOR PROVIDES OVERRIDE OF PLATFORM CONTROLS

2,100 LBS. LIFT CAPACITY IN ALL POSITIONS W/ OUTRIGGER BOOM INTERLOCK

PILOT-OPERATED HYDRAULIC SYSTEM FOR BOOM FUNCTIONS

FULL PRESSURE HYDRAULIC SYSTEM, 3000 PSI CLOSED CENTER W/ LOAD SENSING CAPABILITIES



888-925-0858

www.customtruck.com

*Custom Truck One Source reserves the right to change the specification of any unit at any time without prior notice. This brochure is only a statement of general specifications on the date of this publication.

ASK ABOUT THE CUSTOMIZED AND FLEXIBLE LEASING & FINANCING SOLUTIONS AVAILABLE FROM CUSTOM TRUCK CAPITAL

